

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 13/09/2024 Revision date: 13/09/2024 Supersedes version of: 15/09/2022

Version: 22.1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form Trade name UFI Swiss CPID No Product code Vaporizer Mixture CFR 1 F2CM-G698-GRNJ-WVVJ 254760-81 BU Fire Protection Aerosol



# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.2.1. Relevant identified uses

Main use category Industrial/Professional use spec Use of the substance/mixture Professional use For professional use only Spray cleaners

## 1.2.2. Uses advised against

No additional information available

# 1.3. Details of the supplier of the safety data sheet

Supplier	Department issuing data specification sheet
Hilti (Schweiz) AG	Hilti AG
Soodstrasse 61	Feldkircherstraße 100
CH 8134 Adliswil	FL 9494 Schaan
Schweiz	Liechtenstein
T +41 844 84 84 85, F +41 844 84 84 86	T +423 234 2111
<u>info@hilti.ch</u>	product.compliance-fire.protection@hilti.com

### 1.4. Emergency telephone number

Emergency number

Emergency CONTACT (24-Hour-Number): GBK GmbH Global Regulatory Compliance +49 (0)6132-84463

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity – Single exposure, Category 3, Narcosis Full text of H- and EUH-statements: see section 16 H222;H229 H319 H336



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements	
Labelling according to Regulation (EC) No. 1272	/2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS07
Signal word (CLP)	Danger
Contains	Acetone
Hazard statements (CLP)	H222 - Extremely flammable aerosol.
	H229 - Pressurised container: May burst if heated.
	H319 - Causes serious eye irritation.
	H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	P210 - Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Pressurized container: Do not pierce or burn, even after use.
	P261 - Avoid breathing spray.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
EUH-statements	EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
isobutane (75-28-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Acetone (67-64-1)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
isobutane (75-28-5)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Component	
propane (74-98-6)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

# SECTION 3: Composition/information on ingredients

## 3.1. Substances

Not applicable

# 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Acetone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330- 49	40 – 80	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
isobutane	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	25 – 60	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
propane	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	10 – 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures general	Call a poison center or a doctor if you feel unwell.	
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.	
First-aid measures after skin contact	If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water.	
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
First-aid measures after ingestion	Call a poison center or a doctor if you feel unwell.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects	May cause drowsiness or dizziness.	
Symptoms/effects after eye contact	Eye irritation.	
4.2 Indication of any immediate medical attention and created treatment needed		

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.1. Extinguishing media	
Suitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Special hazards arising from the substa	nce or mixture
Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	Carbon dioxide. Carbon monoxide. Vapours may form explosive mixture with air.
5.3. Advice for firefighters	
Protection during firefighting	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
<b>SECTION 6: Accidental release mea</b>	sures
	news and among a successful a
6.1. Personal precautions, protective equipment	nent and emergency procedures

6.1.1. For non-emergency personnel	
Emergency procedures	Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing spray. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up		
Methods for cleaning up Other information	Take up liquid spill into absorbent material. Dispose of materials or solid residues at an authorized site.	

# 6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and st	orage
7.1. Precautions for safe handling	
Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage conditions	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	5 – 25 °C
7.3. Specific end use(s)	
No additional information available	

No additional information available



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

# 8.1.1. National occupational exposure and biological limit values

Acetone (67-64-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Acetone	
IOEL TWA	1210 mg/m <sup>3</sup>	
	500 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Switzerland - Occupational Exposure Limits		
Local name	Acétone / Aceton	
MAK (OEL TWA)	1200 mg/m <sup>3</sup>	
	500 ppm	
KZGW (OEL STEL)	2400 mg/m <sup>3</sup>	
	1000 ppm	
Critical toxicity	VR, SNC, Yeux / AW, ZNS, Auge	
Notation	B/B	
Remark	NIOSH	
Regulatory reference	www.suva.ch, 01.01.2023	
Switzerland - BAT		
Local name	Acétone / Aceton	
BAT	50 mg/l (1.38 mmol/l; Paramètre biologique: Acétone; Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail.) / (1.38 mmol/l; Biologischer Parameter: Aceton; Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Expositionsende, bzw. Schichtende.)	
Remark	Paramètre non spécifique. / Nicht spezifischer Parameter.	
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte	
isobutane (75-28-5)		
Switzerland - Occupational Exposure Limits		
Local name	iso-Butane / iso-Butan	
MAK (OEL TWA)	1900 mg/m <sup>3</sup>	
	800 ppm	
KZGW (OEL STEL)	7600 mg/m <sup>3</sup>	
	3200 ppm	
Critical toxicity	SNC / ZNS	
Regulatory reference	www.suva.ch, 01.01.2023	



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane (74-98-6)		
Switzerland - Occupational Exposure Limits		
Local name	Propane / Propan	
MAK (OEL TWA)	1800 mg/m <sup>3</sup>	
	1000 ppm	
KZGW (OEL STEL)	7200 mg/m <sup>3</sup>	
	4000 ppm	
Critical toxicity	Formel / Formal	
Remark	NIOSH	
Regulatory reference	www.suva.ch, 01.01.2023	

### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

## 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

# 8.2.2. Personal protection equipment

### Personal protective equipment:

Gloves. Protective clothing. Protective goggles.

Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses			EN 166, EN 171

### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear suitable gloves tested to EN374. Suitable for short-term work or as a splash guard: Nitrile rubber gloves (> 0.2 mm). In case of permanent product contact:



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Protective gloves	Butyl rubber	6 (> 480 minutes)	0,5mm		EN ISO 374

### 8.2.2.3. Respiratory protection

### **Respiratory protection:**

Ensure good ventilation of the work station. If the occupational exposure limit is exceeded: Wear appropriate mask. (e.g. gas filter type A1-P2 according to EN 14387)

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

# Environmental exposure controls:

Avoid release to the environment.

No additional information available

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

5.1. Information on basic physical and one	
Physical state	Liquid
Colour	Colourless.
Appearance	Aerosol.
Odour	characteristic.
Odour threshold	Not available
Melting point	Not applicable
Freezing point	Not available
Boiling point	Not available
Flammability	Extremely flammable aerosol.
Explosive properties	Pressurised container: May burst if heated.
Lower explosion limit	Not available
Upper explosion limit	Not available
Flash point	Not applicable
Auto-ignition temperature	Not available
Decomposition temperature	Not available
рН	Not available
Viscosity, kinematic	Not available
Solubility	Not available
Partition coefficient n-octanol/water (Log Kow)	Not available
Vapour pressure	2500 – 2900 hPa at 20 °C
Vapour pressure at 50°C	Not available
Density	0.74 – 0.76 g/cm <sup>3</sup>
Relative density	Not available
Relative vapour density at 20°C	Not available
Particle characteristics	Not applicable

# 9.2. Other information

## 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients 120 %

# 9.2.2. Other safety characteristics

No additional information available



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

## 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

# 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

11.1. Information on hazard classes as define	ed in Regulation (EC) No 1272/2008
Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 oral	6667 mg/kg
LD50 dermal rabbit	> 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat	132 mg/l (3 h, Rat, Male, Experimental value, Inhalation (vapours))
isobutane (75-28-5)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
CFR 1	
Vaporizer	Aerosol



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 11.2. Information on other hazards

No additional information available

12.1. Toxicity	
Ecology - general	The product is not considered harmful to aquatic organisms nor to cause long-term advers effects in the environment.
Hazardous to the aquatic environment, short-term facute)	Not classified
Hazardous to the aquatic environment, long-term chronic)	Not classified
Acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow- through system, Fresh water, Experimental value, Measured concentration)
EC50 - Crustacea [1]	> 12700 mg/l
ErC50 algae	> 530 mg/l 96h, Pseudokirchneriella subcapitata
isobutane (75-28-5)	
EC50 96h - Algae [1]	8.57 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)
propane (74-98-6)	
EC50 96h - Algae [1]	12 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)
12.2. Persistence and degradability	
Acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
isobutane (75-28-5)	
Persistence and degradability	Readily biodegradable in water.
propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
Acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
isobutane (75-28-5)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane (74-98-6)		
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
12.4. Mobility in soil		
Acetone (67-64-1)		
Surface tension	23.3 mN/m (20 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	
isobutane (75-28-5)		
Surface tension	No data available in the literature	
Ecology - soil	Not applicable (gas).	
propane (74-98-6)		
Surface tension	No data available in the literature	
Ecology - soil	Not applicable (gas).	
12.5. Results of PBT and vPvB assessment		
CFR 1		
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII		
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		

## 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste treatment methods

European List of Waste (LoW, EC 2000/532)

Dispose of contents/container in accordance with licensed collector's sorting instructions. 16 05 04\* - gases in pressure containers (including halons) containing dangerous substances

15 01  $10^{\ast}$  - packaging containing residues of or contaminated by dangerous substances



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### HP Code

HP3 - "Flammable:"

– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and  $\leq$  75 °C;

 – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;

 – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;

– flammable gaseous waste: gaseous waste which is flammable in air at 20  $^\circ C$  and a standard pressure of 101.3 kPa;

- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;

- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

# **SECTION 14: Transport information**

### In accordance with ADR / IMDG / IATA / RID /

ADR	IMDG	ΙΑΤΑ	RID
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS
Transport document description			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information availa	able		

# 14.6. Special precautions for user

### **Overland transport**

Classification code (ADR)	5F
Special provisions (ADR)	190, 327, 344, 625
Limited quantities (ADR)	11
Packing instructions (ADR)	P207, LP02
Mixed packing provisions (ADR)	MP9
Transport category (ADR)	2
Tunnel restriction code (ADR)	D



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport by sea Special provisions (IMDG) Limited quantities (IMDG) Packing instructions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG) MFAG-No	63, 190, 277, 327, 344, 959 SP277 P207, LP02 F-D S-U None 126
Air transport PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA) Special provisions (IATA)	203 75kg 203 A145, A167, A802
Rail transport Special provisions (RID) Limited quantities (RID) Packing instructions (RID)	190, 327, 344, 625 1L P207, LP02

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	
3(a)	CFR 1 ; Acetone	
3(b)	CFR 1 ; Acetone	
40.	Acetone ; isobutane ; propane	

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

## Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors) ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	CAS-No.		Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives\_en

### Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

### 15.1.2. National regulations

#### Switzerland

Swiss National Regulations

Young people in basic vocational training may only work with this product if this is provided for in the respective educational ordinance to achieve their training goal, the requirements of the training plan are met and the applicable age restrictions are observed. Young people who do not complete basic vocational training must not work with this product. Young people are employees of both sexes up to the age of 18 (Ordinance on the Protection of Young People at Work, SR 822.115). 254760-81

Swiss CPID No

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

Indication of changes			
Section	Changed item	Change	Comments
			general update
1		Modified	
8.2		Modified	
15		Modified	
16		Modified	

Abbreviations and acronyms:		
CAS-No.	Chemical Abstract Service number	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:			
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
ED	Endocrine disrupting properties		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
IOELV	Indicative Occupational Exposure Limit Value		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
N.O.S.	Not Otherwise Specified		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
vPvB	Very Persistent and Very Bioaccumulative		
WGK	Water Hazard Class		
VOC	Volatile Organic Compounds		
SDS	Safety Data Sheet		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006		
PNEC	Predicted No-Effect Concentration		
PBT	Persistent Bioaccumulative Toxic		
OEL	Occupational Exposure Limit		
OECD	Organisation for Economic Co-operation and Development		
COD	Chemical oxygen demand (COD)		
ThOD	Theoretical oxygen demand (ThOD)		
TRGS	Technical Rules for Hazardous Substances		
TLM	Median Tolerance Limit		
STP	Sewage treatment plant		

Full text of H- and EUH-statements:		
Aerosol 1	Aerosol, Category 1	



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
EUH066	Repeated exposure may cause skin dryness or cracking.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 2	Flammable liquids, Category 2	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Aerosol 1	H222;H229	On basis of test data	
Eye Irrit. 2	H319	Calculation method	
STOT SE 3	H336	Calculation method	

SDS\_EU\_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.